


KeeService Company has established itself a leader in innovation and dependability in the waste equipment industry. From engineering to production KeeService Company is committed to providing top quality equipment and service.

KeeService Company's neat, clean appearance in both the rear loading model and the front loading model blends attractively with its surroundings.

With the KeeService Company's low 40" loading height, even the most petite person can handle the job. Close the lid, insert the key in the Power Pack console and turn the KeeService Company's powerful hydraulic system on. The packing blade automatically cycles incorporated in the KeeService Company design are unique safety features that prevent the compaction cycle from operating while the loading chamber lid is open.

Another important safety back-up feature is a mushroom STOP button on the Power Pack console that will halt operation at any point in the cycle. The KeeService Company's key-operated system also allows the charge lid to be locked for controlled access.



KS6F SELF CONTAINED COMPACTOR (REAR LOADING)

SPECIFICATIONS


LOADING CHAMBER SIZE	Mfgs. Rating 1.0 Cubic Yard
LOADING CHAMBER OPENING	Length 27 1/2" Width 53 1/2"
LOADING CHAMBER HEIGHT	40"
RAM FACE	Width 53" Height 46"
RAM PENETRATION	0" - 13"
PACKING PRESSURE	Normal 1550 PSI Maximum 1750 PSI
PACKING FORCE	Normal 21,900 Lbs. Maximum 24,700 Lbs.
STANDARD POWER PACK	
1) Electric Motor	3HP 1750 RPM TEFC
2) Control Panel	208/230/460 Volts 3-Phase, 60 Hertz Key Start Switch & Stop Buttons
3) Hydraulic Pump	5GPM HI-LO with 200 Mesh Screen Suction Filter
4) Hydraulic Reservoir	13 Gallons
5) Hydraulic Fluid	Dextron II ATF
6) Power Pack Cover	Protective Metal Cover with Hydraulic Hose Storage Slot
7) Hydraulic Hoses	12' with Quick-Disconnect
HYDRAULIC CYLINDERS	Industrial Hydraulic Couplers
CYCLETIME	2 · 3" x 16" 26 Seconds

FEATURES


CONTAINER CAPACITY	6 Cubic Yards
OVERALL DIMENSIONS	Length 102" Width 82" Height 62"
APPR. SHIPPING WEIGHT WITH POWER PACK	2,280 Lbs.



Compact Weather Proof 3 Phase and/or Single Phase Power Unit. (UL) Approved



Loading Chamber Lid, Spring Assisted for Ease of Opening



Front load: Lid Hold Down Latches for Quick Driver Release When Dumping

Optional Wheel Mounting Kit



KEE Service COMPANY

Kee Service Company
1515 American Way
Cedar Hill, TX 75114
Phone 972-293-0855 / Fax 972-292-9691

Continued product improvement is a KSC goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment and prices. All KSC Compaction Units conform to applicable ANSI 2245.2 safety standards.

